Appl. No. 09/834,593
Amdt. Dated Sep. 03, 2004
Reply to Office action of Aug. 12, 2004

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

Claim 1. (original)   A scanner system for capturing three-dimensional information of an object, comprising:

a projection system projecting a pattern onto said object along a first axis;

an electronic imaging device comprising an array of pixels, said electronic imaging device oriented along a second axis different from said first axis, said electronic imaging device forming an image of said pattern after reflection of said pattern off of said object;

a memory storing a three-axis (X, Y and Z) coordinate system calibration relationship for said scanner, said calibration relationship identifying: (1) pixel coordinates for said electronic imaging device for numerous portions of said pattern, said pixel coordinates associated with distance information from said projection system in a Z direction at at least two different Z distances, and (2) distance information in X and Y directions, for said numerous portions of said pattern, at said at least two different Z distances; and

at least one processing unit processing said image of said pattern and comparing data from said image to said calibration relationship to thereby derive spatial information

OraMetrix, Inc.   Page 2 of 22
2350 Campbell Creek Blvd., Suite 400
Richardson, Texas 75082

in three dimensions of points on said object reflecting said projected pattern onto said electronic imaging device.

Claim 2. (original)   The scanner system of claim 1, wherein said processing system derives said spatial information in three dimensions from said calibration relationship without use of optical characteristics of lens systems associated with said projection system and said electronic imaging device, to thereby compensate for optical distortions present in said lens system.

Claim 3. (original)   The scanner system of claim 1, wherein said calibration relationship (1) is obtained by projection of said pattern onto at least one surface and detecting at least a portion of the pattern with said electronic imaging device with said at least one surface placed at at least two known Z distances from said projection device.

Claim 4. (original)   The scanner system of claim 3, wherein said at least one surface comprises a reference object of known geometry.

Claim 5. (original)   The scanner system of claim 4, wherein said reference object comprises a planar surface.

Claim 6. (original)   The scanner system of claim 3, wherein said reference object comprises a curved surface.

Claim 7. (original)   The scanner system of claim 1, wherein said calibration relationship (2) is obtained, at least in part, by imaging a reference object having a plurality of clearly distinguishable objects spatially separated from each other in X and Y directions at said at least two different Z distances.

Claim 8. (original)   The scanner system of claim 7, wherein said reference object comprises a plane having an array of X-Y points.

Claim 9. (original)   The scanner system of claim 7, wherein said array of points comprises at least four points.

Claim 10. (original)   The scanner system of claim 7, wherein said array of points comprises apertures in a planar surface which are backlit by a source of illumination.

Claim 11. (original)   The scanner system of claim 7, wherein said reference object is moved between said two different Z distances to thereby generate said calibration relationship (2).

Claim 12. (original) The scanner of claim 1, wherein said projection system and said electronic imaging device are contained in a housing sized and shaped to be held in a human hand.

Claim 13. (original) The scanner system of claim 12, wherein said housing further comprises a distal portion holding a mirror, and wherein said distal portion is sized and shaped so as to be insertable into and moveable within an oral cavity of a human so as to enable scanning of anatomical structures inside the oral cavity.

Claim 14. (original) The scanner system of claim 1, wherein said memory and processing unit are located in a scanning workstation, said scanning workstation further comprising a monitor operatively connected to said processing unit, said monitor displaying three-dimensional images of said object during or after said processing unit has derived said spatial information.

Claim 15. (original) The scanner system of claim 1, wherein said projection means illuminates said object at in a series of flashes at a rate of at least one flash per second, and wherein said electronic imaging device captures a series of images of said pattern after reflection from said object at a frame rate substantially in synchronism with said rate.

Claim 16. (original) The scanner system of claim 1, wherein said object comprises a work of art.

Claim 17. (original) The scanner system of claim 1, wherein said object comprises a human body.

Claim 18. (original) The scanner system of claim 1, wherein said object comprises a workpiece.

Claim 19. (original) The scanner system of claim 1, wherein said processing unit executes software performing (1) pattern recognition of images captured by said electronic imaging device, (2) decoding of patterns detected by said pattern recognition software to identify specific portions of said projected pattern captured by said electronic imaging device; and (3) calculation of spatial coordinates in three dimensions for said specific portions of said pattern in accordance with said calibration relationship stored in said memory.

Claim 20. (original) The scanner system of claim 1, wherein said processing unit further executes a registration algorithm for registering three-dimensional spatial coordinates assigned to a first frame derived from a first captured image with three-dimensional spatial coordinates assigned to a second frame derived from a second captured image.

Claim 21. (original) The scanner system of claim 1, wherein said calibration relationship comprises a calibration table, and wherein said calibration table contains pixel coordinates in calibration relationship (1) in sub-pixel resolution.

Claim 22. (original)   The scanner system of claim 21, wherein said calibration table contains said distance information with a resolution greater than 1 millimeter.

Claim 23. (original)   The scanner system of claim 1, wherein a reflective material is applied to said object prior to capturing images of said object with said electronic image converter.

Claim 24. (original)   The scanner system of claim 1, wherein said object comprises a tooth.

Claim 25. (original)   The scanner system of claim 1, wherein said projection pattern portion comprises a series of parallel lines, and wherein said projection pattern contain elements that vary in a direction both parallel to said lines and perpendicular to said lines.

Claim 26. (original)   A method of obtaining three-dimensional surface information of an object, comprising the steps of:

Page 7 of 22

positioning a scanner proximate to said object, said scanner having a projection

system for projecting a pattern onto said object and an electronic imaging device

generating two dimensional images of the reflection of said pattern off of said surface;

moving said scanner and object relative to each other;

capturing, with said electronic imaging device, a series of two dimensional

images of said projection pattern after reflection of said pattern off of said object as said

scanner and said surface move relative to each other;

processing said series of images to obtain a series of frames of said object, each

frame comprising spatial coordinates for a portion of the surface of said object in three

dimensions, and

registration overlapping areas of said frames to each other to generate a three-

dimensional virtual model of said object.

Claim 27. (original)   The method of claim 26, wherein said series of images are

captured at a rate of at least one image per second and wherein said pattern is projected

onto said object in a series of flashes timed at a rate in synchronism with said image

capture rate.

Claim 28. (original)   The method of claim 27, wherein after initiation of said series of

flashes said flashes continue automatically without human intervention.

Claim 29. (original) The method of claim 26, wherein said step of processing further comprises a step of executing a decoding algorithm identifying specific portions of said projected pattern captured by said electronic imaging device after reflection from said object.

Claim 30. (original) The method of claim 26, further comprising the step of storing a calibration relationship for said scanner wherein said processing system derives said spatial information in three dimensions from said calibration relationship without use of optical characteristics of lens systems associated with said projection system and said electronic imaging device, to thereby compensate for optical distortions present in said lens system.

Claim 31. (original) The method of claim 30, wherein said calibration relationship comprises a mathematical function providing Z distance information and X and Y values from input comprising pixel addresses in said electronic imaging device.

Claim 32. (original) The method of claim 30, wherein said calibration relationship comprises a calibration table.

Claim 33. (original) The method of claim 26, further comprising the step of providing a data storage medium storing two dimensional images obtained by said electronic imaging device needed to cover said object.

Claim 34. (original) The method of claim 26, wherein said step of processing comprising the steps of:

a) performing pattern recognition of said series of images to detect features of said projected pattern in each of said images,

b) decoding of patterns detected by said pattern recognition step to identify specific portions of said projected pattern captured by said electronic imaging device; and

c) calculation of spatial coordinates in three dimensions for said specific portions of said decoded patterns.

Claim 35. (original) The method of claim 34, wherein said step of calculation comprises comparing decoded points of said projected pattern captured by said electronic imaging device with calibration values stored in a calibration table stored in a memory for said scanner.

Claim 36. (original) The method of claim 34, wherein each two-dimensional image captured by said electronic imaging device is converted to a frame in accordance with said calculation step, and wherein said series of frames are stored in a memory, and wherein the method further comprises the step of executing a registration algorithm to register said series of frames to derive a three-dimensional model of the surface of said object.

Claim 37. (original)   The method of claim 26, wherein said scanner comprises a hand-held unit.

Claim 38. (original)   The method of claim 26, wherein said scanner is used to obtain a three-dimensional model of an anatomical structure.

Claim 39. (original)   The method of claim 38, wherein said anatomical structure comprises teeth.

Claim 40. (original)   The method of claim 39, wherein said teeth are scanned in-vivo with said scanner.

Claim 41. (original)   The method of claim 39, wherein a physical model is made from said anatomical structure and wherein said scanner scans said physical model.

Claim 42. (original)   The method of claim 41, wherein said physical model comprises a model of a patient's teeth and surrounding anatomical structures.

Claim 43. (original)   A method of calibration of a scanner, said scanner comprising a projection system for projecting a pattern and an electronic imaging device for generating

an image of said pattern after reflection of said pattern from an object, comprising the steps of:

projecting said pattern onto at least one surface at two different distances from said scanner and generating first and second images with said electronic imaging device of said pattern at said two distances;

imaging a set of objects of known spatial X-Y relationship at said two different differences;

generating a three-axis (X, Y and Z) coordinate system calibration relationship for said scanner, said calibration relationship indicating: (1) pixel coordinates for numerous portions of said pattern when said pattern is projected onto said surface at said two different distances, and (2) distance information in X and Y directions for said portions of said pattern for said two different distances; and

storing said calibration relationship in a memory associated with said scanner.

Claim 44. (original) The method of claim 43, wherein said set of objects of known spatial X-Y relationship comprises an array of points lying in a plane and separated from each other by a known distance.

Claim 45. (original) The method of claim 44, where said step of generating said calibration relationship comprises the step of interpolating said distance information in X and Y directions for portions of said pattern from said images of said array of points.

Page 12 of 22

Claim 46. (original) The method of claim 43, wherein said pixel coordinates for said numerous portions of said pattern are obtained by performing the following steps:

a) performing pattern recognition of said first and second images to detect features of said projected pattern in each of said images, and

b) associating said specific portions of said projected pattern to specific pixels, or sub-pixels, of said electronic imaging device.

Claim 47. (original) The method of claim 44, wherein said array of points comprises a back-lit, planar surface having a plurality of apertures arranged in an array and separated from each other by a known distance.

Claim 48. (original) The method of claim 43, wherein said scanner comprises a hand-held scanner.

Claim 49. (original) The method of claim 47, wherein said scanner remains fixed in position and wherein said flat planar surface and said back-lit surface are moved back and forth relative to said scanner to achieve said first and second distances.

Claim 50. (original) A calibration apparatus for a scanner, said scanner having a projection system for projecting a pattern and a electronic imaging device for capturing images of said pattern after reflection of said pattern off an object, comprising:

at least one calibration surface comprising a Z calibration surface and an X-Y calibration surface, and wherein the calibration station further comprises:

a carrier system holding said Z calibration surface and said X-Y calibration surface and moving said Z calibration surface and said X-Y calibration surface relative to said scanner between two different distances from said scanner;

said carrier system further comprising a drive mechanism for moving either said Z calibration surface or said X-Y calibration surface into the optical path of said scanner.

Claim 51. (original) The calibration station of claim 50, wherein said Z calibration surface comprises a smooth, flat, planar reflective surface.

Claim 52. (original) The calibration station of claim 50, wherein said X-Y calibration surface comprises a back-lit, planar surface having a plurality of apertures arranged in an array and separated from each other by a known distance.

Claim 53. (original) The calibration station of claim 50, wherein said X-Y calibration surface comprises planar surface having a plurality of light sources arranged in an array and separated from each other by a known distance.

Claim 54. (original) A machine-readable memory for a scanner used to calculate three dimensional information of an object scanned by said scanner, said scanner having a projection system for projecting a pattern onto an object and a electronic imaging device

Page 14 of 22

for imaging said pattern after reflection of said pattern from said object, said memory comprising:

an array of data storage locations containing a three-axis (X, Y and Z) coordinate system calibration relationship for said scanner,

said calibration relationship identifying: (1) pixel coordinates for said electronic imaging device for numerous portions of said pattern, said pixel coordinates associated with distance information from said projection system in a Z direction at at least two different Z distances, and (2) distance information in X and Y directions, for said numerous portions of said pattern, at said at least two different Z distances.

Claim 55. (original) The machine-readable memory of claim 54, wherein said calibrtation relationship comprises a calibration table.

Claim 56. (original) The machine-readable memory of claim 54, wherein said memory is incorporated into a scanning work station coupled to said scanner.

Claim 57. (original) The machine-readable memory of claim 54, wherein said memory is incorporated into said scanner.

Claim 58. (original) The machine-readable memory of claim 54, wherein said memory is incorporated into a computer remote from said scanner and receiving data from said

OraMetrix, Inc.   Page 15 of 22
2350 Campbell Creek Blvd., Suite 400
Richardson, Texas 75082

scanner, said computer calculating surface geometry of an object scanned by said scanner

in accordance with said table.

Claim 59. (original)   A machine-readable memory accessible by a computing device,

said memory comprising data storage regions storing surface information in three

dimensions of at least a portion of a work of art, said surface information obtained by

scanning said work of art with a scanner and calculating said surface information in three

dimensions from a series of images obtained by said scanner.

Claim 60. (original)   The machine-readable memory of claim 59, wherein said memory

comprises a library of surface information in three dimensions for a plurality of works of

art.

Claim 61. (original)   The machine-readable memory of claim 59, wherein said scanner

comprises a hand-held scanner.

Claim 62. (currently amended)   The machine-readable memory of clam [[59]]60,

wherein said work of art is authenticated using said library of said plurality of works of

art.

Claim 63. (original)   The machine-readable memory of claim 59, wherein said work of

art comprises a sculpture.

Claim 64. (original)   The machine-readable memory of claim 59, wherein said surface

information is obtained by a scanner calibrated in accordance with the method of claim

43.

Claim 65. (original)   A calibration device for a scanner, wherein said scanner has a

projection system for projecting a pattern and an electronic imaging device for capturing

images of said pattern after reflection of said pattern off an object, the calibration device

comprising:

a Z calibration surface receiving said projected pattern moveable relative to said

scanner between at least two Z distances separated by a known amount; and

a plurality of detectable features of known X-Y spatial relationship positioned

with respect to said scanner at a known Z distance relative to said Z calibration surface.

Claim 66. (original)   A calibration device for a scanner, wherein said scanner has a

projection system for projecting a pattern and an electronic imaging device for capturing

images of said pattern after reflection of said pattern off an object, the calibration device

comprising:

a Z calibration surface receiving said projected pattern and having a spatial extent

reflecting said pattern at at least two Z distances separated by a known amount; and

Page 17 of 22

a plurality of detectable features of known X-Y spatial relationship positioned at

at least two known Z distances relative to said Z calibration surface.

Claim 67. (original)   The calibration device of claim 65, wherein said Z calibration

surface comprises a planar surface.

Claim 68. (original)   The calibration device of claim 65 or claim 66, wherein said Z

calibration surface includes said plurality of detectable features of known X-Y spatial

relationship.

Claim [[68]]69. (currently amended) The calibration device of claim 65 or claim 66,

wherein said Z calibration surface and said plurality of detectable features of known X-Y

spatial relationship comprise distinct objects.

Claim [[69]]70. (currently amended) The calibration device of claim 65 or claim 66,

wherein said plurality of detectable feature comprise 4 or more detectable features.

Claim [[70]]71. (currently amended)   The calibration device of claim 65 or claim 66

wherein said plurality of detectable features comprise an array of points placed on a

surface.

Claim [[70]]72. (currently amended) The calibration device of claim 65 or claim 66, wherein said plurality of detectable features of known X-Y spatial relationship are printed on an object.

Claim [[71]]73. (currently amended) The calibration device of claim 65 or claim 66, wherein said plurality of detectable features of known X-Y spatial relationship are formed on a surface of an object by a laser.

Claim [[72]]74. (currently amended) The calibration device of claim 65 or claim 66, wherein said Z calibration surface comprises a curved surface.

Claim [[73]]75. (currently amended) The calibration device of claim 66, wherein said Z calibration surface comprises an plurality of planar parallel surfaces.

Claim [[74]]76. (currently amended) The calibration device of claim 65 or claim 66, wherein said calibration device is used to calibrate a scanning system in which the spatial relationship of the projection and imaging axes is not known precisely.

Claim [[75]]77. (currently amended) The calibration device of claim 65 or claim 66, wherein said Z calibration surface has a spatial extent in X and Y directions such that the field of view of said electronic imaging device is completely filled by said Z calibration surface at said two different distances.

Claim [[76]]78. (currently amended) The calibration device of claim 65 or claim 66, wherein said two Z distances is such that the combined depth of focus of the imaging device and the projection device encompasses said two Z distances.

Claim [[77]]79. (currently amended) The calibration device of claim 65 or claim 66, wherein said plurality of detectable features of known X-Y spatial relationship are arranged on an object such that they are spatially extending in X and Y directions on said object at said two different distances at least equal to the field of view of said electronic imaging device.

Claim [[78]]80. (currently amended) The calibration device of claim 65 or claim 66, wherein said plurality of detectable features of known X-Y spatial relationship comprise an array of dots printed on a surface.

Claim [[79]]81. (currently amended) The apparatus of claim 1 wherein said scanner further comprises source of general illumination.

Claim [[80]]82. (currently amended) The method of claim 26, wherein said scanner further comprises a source of general illumination.

Claims 83-88. (canceled)